



## Brake Tubing & Fasteners



Cupro-Nickel



Copper

### Brake Tubing

Brake pipe coils available in copper & 90/10 copper-nickel material manufactured to BSEN 12449 CW024A and CW352 H respectively.

Coils are available in metric & imperial sizes along with 20 or 22 gauge thickness.


Seamless tubes offering better resistance to corrosion and splitting. Easy to bend, flare & install. 100% electronically & pressure tested for pin holes.

## BRAKE FASTENERS

### BRAKE NUTS

**Size: 10mm x 1.00mm Pitch**

- Short Male Nut
- Long Male Nut
- Fully Threaded Male Nut
- Female Nut



**Size: 10mm x 1.25mm Pitch**

- Short Male Nut
- Long Male Nut
- Fully Threaded Male Nut
- Female Nut



**Size: 12mm x 1.00m Pitch**

- Male Nut



**Size: 3/8" UNF x 24tpi Pitch**

- Short Male Nut
- Long Male Nut
- Female Nut



**Size: 7/16" UNF x 20tpi Pitch**

- Male Nut
- Female Nut



### BRAKE CONNECTORS

**Size: 10mm x 1.00mm Pitch**

- Male 2-Way
- Female 2-Way
- Female 3-Way



**Size: 3/8" UNF x 24tpi Pitch**

- Female 2-Way
- Female 3-Way



All the Brake Nuts & Connectors are suitable for 3/16" pipes

### BRAKE BLEED SCREWS

Type	Pitch	Length
M6	1mm	26mm
M7	1mm	21.7mm
M8	1.25mm	26.5mm
M10	1mm	30mm
1/4" UNF	28 tpi	28mm
3/8" UNF	24 tpi	31mm

