



Single Core APC Conductor EBXL-XLPE 120°C Insulated, XLPVC 120°C Sheathed (UA) Solar Cable



Specification of Single Core APC Conductor

Applications:

Transmission and distribution of Power in PV Solar segment Indoor and outdoor uses Cable ducts, cable trays and conduits Direct burial.

Construction:

Conductor : Annealed Plain Copper conductor complying with IEC - 60228
Insulation : EBXL-XLPE 120°C
Jacket : XLPVC 120°C (Black)

Features:

Electron Beam Cross Linked. Does not melt or drip Enhanced Mechanical, Electrical, Thermal & Weathering properties.
Flame retardant
Excellent UV and Ozone resistant.
Specially designed for PV Power cable segment Extra UV & 120°C Continuous rating

Technical Data:

Operating Temperature : -15°C to +120°C
High Insulation resistance at elevated temperature Short Circuit Temperature 280°C
Bending radius (min) : 9 x Cable dia
Test Voltage . 3 kV for 5 mins.



Specification of Single Core APC Conductor

Part Number	Number Of Cores And Mm2 Per Conductor	Outer Diameter in mm approx.	Copper Weight Kg/Km (Nom.)	Weight Kg/Km approx.
688 28 XX	1C X 16	10.0	135	213
688 30 XX	1C X 25	11.5	211	308
688 32 XX	1C X 35	12.6	295	403
688 34 XX	1C X 50	14.2	422	549
688 37 XX	1C X 70	16.0	591	739
688 38 XX	1C X 95	18.0	802	977
688 41 XX	1C X 120	19.7	1013	1211
688 42 XX	1C X 150	21.8	1266	1505
688 44 XX	1C X 185	24.0	1562	1837
688 46 XX	1C X 240	26.8	2027	2352
688 48 XX	1C X 300	30.0	2533	2919
688 49 XX	1C X 400	33.6	3378	3839
688 50 XX	1C X 500	37.2	4222	4766
688 51 XX	1C X 630	41.5	5320	5981

Please replace XX in the part number as per the colour code given hereunder.

Red - 01	Yellow - 02	Blue - 033	Black - 04	Green - 05	Yellow - Green - 06	Grey - 07
----------	-------------	------------	------------	------------	---------------------	-----------